

PRODUCT INFORMATION



See anchorwall.com for installation instructions.

Renowned for its rough-hewn face and earthen tones, the Diamond Pro Stone Cut[®] retaining wall system imparts a rich, faceted beauty not commonly found in commercial retaining walls.

The performance characteristics make it the proven solution for tall walls, Department of Transportation projects, commercial developments, water applications and other critical wall needs.

- Original rear-lip technology

- Can be used to build gravity walls up to 4 feet, including buried course
- Taller walls can be built using geosynthetic reinforcement or the AnchorplexTM retaining wall system when designed by a qualified engineer
- Minimum inside radius 7 feet. Minimum outside radius 4 feet.
- ICC evaluated



Units	Stretcher	Cap	Corner
Approximate Dimensions*	8" x 18" x 12"	Front, 4" x 17 ¹ / ₄ " x 10 ³ / ₈ " Back, 4" x 12" x 10 ³ / ₈ "	8" x 18" x 9" 8" x 18" x 9"
Approximate Weight*	77 lbs.	40 lbs.	101 lbs.
Coverage	1.0 sq. ft.	1.22 lin. ft.	
Setback/System Batter	1"/7.1°		

*Actual dimensions and weight may vary from these approximate dimensions due to variations in manufacturing processes. Specifications may change without notice. See your Anchor representative for details, color options, block dimensions and additional information.

© 2010 Anchor Wall Systems, Inc. The Diamond Pro Stone Cut[®] retaining wall system is manufactured under license from Anchor Wall Systems, Inc. (AWS). The "Anchor Build Something Beautiful" logo, "Anchorplex" and "Diamond Pro Stone Cut" are trademarks of AWS. The wall system blocks are covered by the AWS Limited Warranty. For a complete copy, visit your local dealer or see anchorwall.com.

Anchor Wall Systems, Inc., 5959 Baker Road, Suite 390, Minnetonka, MN 55345.
A&B0810