

PRODUCT INFORMATION


Architects, engineers and contractors are choosing the Diamond Pro® retaining wall system to create flexible, cost-effective solutions for a broad range of large commercial, municipal and residential retaining wall projects. For contours that shape new environments and colors that blend with the surroundings, the natural choice is Diamond Pro blocks.

Aesthetically, the natural rock texture and earth-tone colors blend easily into any environment. Diamond Pro products can be used with geosynthetic reinforcement for tall-wall applications.

- One square foot of wall face per block
- Can be used to build gravity walls up to 4 feet high, including buried course.

- Taller walls can be built using geosynthetic reinforcement or stabilized aggregate when designed by a qualified engineer
- ICC evaluated

Visit anchorwall.com for installation instructions.



*Actual dimensions and weight may vary from these approximate dimensions due to variations in manufacturing processes. Specifications may change without notice. See your Anchor representative for details, color options, block dimensions and additional information.

© 2009 Anchor Wall Systems, Inc. The Diamond Pro® wall system is manufactured under license from Anchor Wall Systems, Inc. (AWS). The "Anchor Build Something Beautiful" logo and "Diamond Pro" are trademarks of AWS. The wall system blocks are covered by the AWS Limited Warranty. For a complete copy, visit your local dealer or see anchorwall.com.

Anchor Wall Systems, Inc., 5959 Baker Road, Suite 390, Minnetonka, MN 55345.


Stretcher Units

Approximate Dimensions*
 Approximate Weight
 Coverage
 Setback/Batter

Beveled Face

8" x 18" x 12"
 72 lbs.
 1.0 sq. ft.
 1"/7.13°

Straight Face

8" x 18" x 12"
 74 lbs.
 1.0 sq. ft.
 1"/7.13°


Accessory Units

Approximate Dimensions*
 Approximate Weight
 Coverage

Cap

Front, 4" x 17¹/₄" x 10³/₈"
 Back, 4" x 12" x 10³/₈"
 40 lbs.
 1.22 linear ft.

Corner

8" x 18" x 9"
 101 lbs.